

20' RENAISSANCE (SWIM SPA) ALL TILED SPA - Fits 13 Adults

SPECIFICATIONS	
DRY WEIGHT:	3600 LBS.
TOTAL WEIGHT:	25988 LBS.
WATER VOLUME:	2685.3 GAL.
WEIGHT:	359 Cu.Ft.
SURFACE AREA:	133.1 SQ. FT.
IAPMO#:	1138
FDA#:	2030305
SKID SUPPORT STRUCTURE BONDED TO SPA	
<input checked="" type="checkbox"/> SKIDS SUPPLIED BY NCSH.	
LIGHT NICHE	
SPA BRIGHT, 120 V, 100 WATT, 50' COORD., U.L. APPROVED	
MAIN DRAIN	
AquaStar 32CDFR, 32" Channel Drain, Approved Max Flow Rate: 1800 GPM @ 3.4 fpm, 136 GPM @ 1.9 fpm, V.G.B. Approved Safety Drain	
SIDEWALL SUCTION	
AquaStar 84V, 8" Dia Frame, Approved Max Flow Rate: FLOW = 88 GPM @ 3.2 fpm, WALL = 70 GPM @ 2.6 fpm, 8.8 Sq Ft - Open Area, V.G.B. Approved Safety Drain	
EQUALIZER	
2" EQUALIZER SUCTIONS, Waterway, 640-3574V, Super HiFlo Suction Assy, Max Flow: 180 GPM, Complies w/ ANSI Code ASME A112.19.8.2009	
SKIMMER	
W/ FORWARD 2F-1084P/VE SURFACE SKIMMER W/ EQUALIZER, NSF APPROVED	
JET	
HYDRO JETTER, 1-1/2" WATER, 1-1/2" AIR, HYDROJAC #10202, COMPLES W/ ANSI CODE ASME A112.19.8.2009, U.L. APPROVED	
RETURN	
INLET FITTINGS, 1-1/2" WALL TYPE W/ EYEBALL, HYDROJAC #10202, COMPLES W/ ANSI CODE ASME A112.19.8.2009, U.L. APPROVED	
FILL	
INLET FITTINGS, 1-1/2" WALL TYPE W/ EYEBALL, HYDROJAC #10202, COMPLES W/ ANSI CODE ASME A112.19.8.2009, U.L. APPROVED	

