












SPECIFICATIONS	
SHELL WEIGHT:	2900 LBS.
WATER WEIGHT:	11574 LBS.
TOTAL SHELL & WATER WEIGHT:	14474.2 LBS.
WATER VOLUME:	232 Cu.Ft.
WATER GALLONS:	1735 GAL.
SURFACE AREA:	89.5 SQ. FT.
ICC ES LISTED #:	PMG-1161

NESPA ENTERPRISES, Inc.

 ICC ES Listed  
PMG-1161

<b>WATERPROOF SKID SUPPORT STRUCTURE ATTACHED TO SPA AT NESPA FACTORY</b>	
<input checked="" type="checkbox"/>	SKIDS SUPPLIED BY NESPA
<b>LIGHT NICHE</b>	
	SPA BRIGHT, 120 V, 100 WATT, 50° CORD, U.L. APPROVED
<b>MAIN DRAIN</b>	
	AquaStar 32CDPLFR, 32" Channel Drain Approved Max Flow Rate: Floor = 236 GPM @ 3.4 fps Wall = 136 GPM @ 1.9 fps Complies w/ ANSI / ASME A112.19.8 & NSF / ANSI 16-2011
<b>MAIN DRAIN SUMP</b>	
	Nespa Aquastar Approved Sump IAPMO Approval # SP4900
<b>SIDEWALL SUCTION</b>	
	AquaStar WAV9, 9" X 9" Frame, Approved Max Flow Rate: Floor = 316 GPM Wall = 203 GPM Complies w/ ANSI / ASME A112.19.8 & NSF / ANSI 16-2011
<b>SIDEWALL SUMP</b>	
	Nespa Aquastar Approved Sump IAPMO Approval # SP4900
<b>EQUALIZER</b>	
	6" Round Hockey Puck AquaStar 6HPHAKXX Sumpplex Suction Outlet Floor 177 GPM Wall 122 GPM Complies w/ ANSI / ASME A112.19.8 & NSF / ANSI 16-2011
<b>SKIMMER</b>	
	HAYWARD SP-1084FVE SURFACE SKIMMER W/ EQUALIZERS, NSF / ANSI 50-2012
<b>JET</b>	
	<b>HYDRO INLETS</b> 1-1/2" WATER - 1-1/2" AIR HYDROAIR #10-5100 COMPLIES W/ ANSI CODE ASME A112.19.8-07 UL APPROVED
<b>RETURN</b>	
	<b>INLET FITTINGS</b> 1-1/2" WALL TYPE W/ EYEBALL HYDROAIR #10-3500 COMPLIES W/ ANSI CODE ASME A112.19.8-07 UL APPROVED
<b>FILL</b>	
	<b>INLET FITTINGS</b> 1-1/2" WALL TYPE W/ EYEBALL HYDROAIR #10-3500 COMPLIES W/ ANSI CODE ASME A112.19.8-07 UL APPROVED

