

SPECIFICATIONS	
SHELL WEIGHT:	3400 LBS.
WATER WEIGHT:	15815 LBS.
TOTAL SHELL & WATER WEIGHT:	19214.7 LBS.
WATER VOLUME:	317 Cu.Ft.
WATER GALLONS:	2371 GAL.
SURFACE AREA:	119.5 SQ. FT.
ICC ES LISTED #:	PMG-1161

NESPA ENTERPRISES, Inc.



ICC ES Listed
PMG-1161

WATERPROOF SKID SUPPORT
STRUCTURE ATTACHED TO
SPA AT NESPA FACTORY

*SKIDS SUPPLIED
BY NESPA

LIGHT NICHE

SPA BRIGHT, 120 V,
100 WATT, 50' CORD,
U.L. APPROVED

MAIN DRAIN

AquaStar 3200DFR, 32" Channel Drain,
Approved Max Flow Rate: Floor = 236 GPM
@ 3.4 f/s Wall = 136 GPM @ 1.9 f/s
Complies w/ ANSI / ASME A112.19.8
& NSF / ANSI 16-2011

MAIN DRAIN SUMP

Nespa Aquastar Approved Sump
IAPMO Approval # SP4900

SIDEWALL SUCTION

AquaStar WAV9, 9" X 9" Frame,
Approved Max Flow Rate:
Floor = 316 GPM
Wall = 208 GPM
Complies w/
ANSI / ASME A112.19.8
& NSF / ANSI 16-2011

SIDEWALL SUMP

Nespa Aquastar Approved Sump
IAPMO Approval # SP4900

EQUALIZER

8" Round Hockey Puck
AquaStar 64PH4000
Sumpless Suction Outlet
Floor 177 GPM
Wall 122 GPM
Complies w/
ANSI / ASME A112.19.8
& NSF / ANSI 16-2011

SKIMMER

HAYWARD SP-1084FVE
SURFACE SKIMMER
W/ EQUALIZERS
NSF / ANSI 50 - 2012

JET

HYDRO INLETS
1-1/2" WATER - 1-1/2" AIR
HYDROAIR #10-5100
COMPLIES W/ ANSI CODE ASME A112.19.8-07
UL APPROVED

RETURN

INLET FITTINGS
1-1/2" WALL TYPE W/ EYEBALL
HYDROAIR #10-3500
COMPLIES W/ ANSI CODE ASME A112.19.8-07
UL APPROVED

FILL

INLET FITTINGS
1-1/2" WALL TYPE W/ EYEBALL
HYDROAIR #10-3500
COMPLIES W/ ANSI CODE ASME A112.19.8-07
UL APPROVED

