



Approved for Commercial use
Complies with VGB Pool
& Spa Safety Act

SPECIFICATIONS	
SHELL WEIGHT:	3850 LBS.
WATER WEIGHT:	19357 LBS.
TOTAL SHELL & WATER WEIGHT:	23206.8 LBS.
WATER VOLUME:	388 Cu.Ft.
WATER GALLONS:	2902 GAL.
SURFACE AREA:	150.0 SQ. FT.
ICC ES LISTED #:	PMG-1161



WATERPROOF SKID SUPPORT STRUCTURE ATTACHED TO SPA AT NESPA FACTORY
*SKIDS SUPPLIED BY NESPA

LIGHT NICHE
SPA BRIGHT, 120 V, 100 WATT, 50' CORD, U.L. APPROVED

MAIN DRAIN
AquaStar 32CDFLR, 32" Channel Drain, Approved Max Flow Rate: Floor = 236 GPM @ 3.4 fps Wall = 136 GPM @ 1.9 fps Complies w/ ANSI / ASME A112.19.8 & NSF / ANSI 16-2011

MAIN DRAIN SUMP
Nespa Aquastar Approved Sump IAPMO Approval # SP4900

SIDEWALL SUCTION
AquaStar WAV9, 9" X 9" Frame, Approved Max Flow Rate: Floor = 316 GPM Wall = 208 GPM Complies w/ ANSI / ASME A112.19.8 & NSF / ANSI 16-2011

SIDEWALL SUMP
Nespa Aquastar Approved Sump IAPMO Approval # SP4900

EQUALIZER
6" Round Hockey Puck AquaStar 6HPHxxx Sumpless Suction Outlet Floor 177 GPM Wall 122 GPM Complies w/ ANSI / ASME A112.19.8 & NSF / ANSI 16-2011

SKIMMER
HAYWARD SP-1084FVE SURFACE SKIMMER W/ EQUALIZERS, NSF / ANSI 50 - 2012

JET
HYDRO INLETS 1-1/2" WATER - 1-1/2" AIR HYDROAIR #10-5100 COMPLIES W/ ANSI CODE ASME A112.19.8-07 U.L. APPROVED

RETURN
INLET FITTINGS 1-1/2" WALL TYPE W/ EYEBALL HYDROAIR #10-3500 COMPLIES W/ ANSI CODE ASME A112.19.8-07 U.L. APPROVED

FILL
INLET FITTINGS 1-1/2" WALL TYPE W/ EYEBALL HYDROAIR #10-3500 COMPLIES W/ ANSI CODE ASME A112.19.8-07 U.L. APPROVED

