














SPECIFICATIONS	
SHELL WEIGHT:	2650 LBS.
WATER WEIGHT:	9379 LBS.
TOTAL SHELL & WATER WEIGHT:	12029.1 LBS.
WATER VOLUME:	188 Cu.Ft.
WATER GALLONS:	1406 GAL.
SURFACE AREA:	74.5 SQ. FT.
ICC ES LISTED #:	PMG-1161

NESPA ENTERPRISES, Inc.



ICC ES Listed
PMG-1161

- WATERPROOF SKID SUPPORT STRUCTURE ATTACHED TO SPA AT NESPA FACTORY
-   *SKIDS SUPPLIED BY NESPA
- LIGHT NICHE**
 SPA BRIGHT, 120 V, 100 WATT, 50' CORD, U.L. APPROVED
- MAIN DRAIN**
 AquaStar 320DFR, 32" Channel Drain, Approved Max Flow Rate: Floor = 236 GPM @ 3.4 fps Wall = 136 GPM @ 1.9 fps Complies w/ ANSI / ASME A112.19.8 & NSF / ANSI 16-2011
- MAIN DRAIN SUMP**
 Nespa Aquastar Approved Sump IAPMO Approval # SP4900
- SIDEWALL SUCTION**
 AquaStar WAV9, 9" X 9" Frame, Approved Max Flow Rate: Floor = 316 GPM Wall = 208 GPM Complies w/ ANSI / ASME A112.19.8 & NSF / ANSI 16-2011
- SIDEWALL SUMP**
 Nespa Aquastar Approved Sump IAPMO Approval # SP4900
- EQUALIZER**
 6" Round Hockey Puck AquaStar 6HPHxxx Sumpless Suction Outlet Floor 177 GPM Wall 122 GPM Complies w/ ANSI / ASME A112.19.8 & NSF / ANSI 16-2011
- SKIMMER**
 HAYWARD SP-1084FVE SURFACE SKIMMER W/ EQUALIZERS, NSF / ANSI 50 - 2012
- JET**
 HYDRO INLETS 1-1/2" WATER - 1-1/2" AIR HYDROAIR #10-5100 COMPLIES W/ ANSI CODE ASME A112.19.8-07 UL APPROVED
- RETURN**
 INLET FITTINGS 1-1/2" WALL TYPE W/ EYEBALL HYDROAIR #10-3500 COMPLIES W/ ANSI CODE ASME A112.19.8-07 UL APPROVED
- FILL**
 INLET FITTINGS 1-1/2" WALL TYPE W/ EYEBALL HYDROAIR #10-3500 COMPLIES W/ ANSI CODE ASME A112.19.8-07 UL APPROVED

