2800 Richter Ave. Suite C Oroville, CA 95966

Office: (530) 534-9910 Fax: (530) 534-9915 E-Mail: sales@tiledspas.com www.tiledspas.com

## 8' ROUND

## SPA DETAIL


\*ALL DIMENSIONS SUBJECT TO 1/4" TOLERANCES\*

SCALE: 1/2" = 1'-0"

DATE: 02/10/05

JOB:

DR#:



2800 Richter Ave. Suite C Oroville, CA 95966

Office: (530) 534-9910 Fax: (530) 534-9915 E-Mail: sales@tiledspas.com www.tiledspas.com

# 8' ROUND

### PLUMBING DETAIL


\*ALL DIMENSIONS SUBJECT TO 1/4" TOLERANCES\*

SCALE: 1/2" = 1'-0"

DATE: 02/10/05

JOB:

DR#:



2800 Richter Ave. Suite C Oroville, CA 95966

Office: (530) 534-9910 Fax: (530) 534-9915 E-Mail: sales@tiledspas.com www.tiledspas.com

## 10' ROUND


### SPA DETAIL

\*ALL DIMENSIONS SUBJECT TO 1/4" TOLERANCES\*

SCALE: 3/8" = 1'-0" DATE: 02/10/05


JOB:


DR#:



#### SPECIFICATIONS

DRY WEIGHT: 1800 lbs. WET WEIGHT: 13 590 lbs WATER: 1420 GALLONS SURFACE AREA: 80 sq.ft. IAPMO#: 1138 FDA#: 2030305





2800 Richter Ave. Suite C Oroville, CA 95966

Office: (530) 534-9910 Fax: (530) 534-9915 E-Mail: sales@tiledspas.com www.tiledspas.com

# 10' ROUND


### PLUMBING DETAIL

SCALE: 1/2" = 1'-0"

DATE: 02/10/05

JOB:

DR#: \*ALL DIMENSIONS SUBJECT TO 1/4" TOLERANCES\*



1		I	I	1
ITEM	DESCRIPTION	MANUFACTURER	CATALOG NO.	QTY.
Α	LIGHT NICHE (FOR UNDERWATER LIGHT) W/ 1" HUB	PENTAIR/PACFAB	782423	1
В	SPA BRIGHT UNDERWATER LIGHT, 120 VOLT, 100 WATT, 50' CORD, U.L. APPROVED	PENTAIR/PACFAB	78108100	1
С	LIGHT J-BOX	PENTAIR/PAC FAB	78310700	1
D	SURFACE SKIMMER W/ EQUALIZER, NSF APPROVED	HAYWARD	SP-1084 FVE	1
Е	4" ANTI VORTEX EQUALIZIER 3.61 SQ.IN. OPEN AREA, COMPLIES W/ ANSI CODE A112.19	HYDROAIR	10-6806	2
F	HYDRO INLETS, 1 1/2" WATER, 1 1/2" AIR	HAYWARD	10-5100	7
G	INLET FITTINGS, 1 1/2", WALL TYPE, W/ EYEBALL	HYDRO AIR	10-3500	3
Н	5" HIGH FLOW ANTI VORTEX SUCTIONS 8.39 SQ. IN. OPEN AREA 208 GPM AT 1.5 FT/SEC WATER VELOCITY, COMPLIES W/ ANSI CODE A112.19 UL APPROVED	WATERWAY	640-3850	4
I	HAND RAIL, STAINLESS STEAL, 4' 0" LENGTH, W/ .065TUBING WALL THICKNESS	S.R. SMITH	DMS-102	2
J	WEDGE ANCHORS, BRONZE	S.R. SMITH	EP-100A	4
L	COPING TILE ON TOP HORIZONTAL EDGE OF SPA	DAL	C701	
М	MAIN DRAIN GRATE, 12" X 12" FRAME, 85 SQ. IN. OPEN AREA, 401 GPM @1 1/2 FT/SEC	PAC FAB	54-2020	1
N	NATURAL GAS HEATER W/ POWER ASSISTED VENTILATION, 150K BTU	PAC FAB	PEN 460553	1
Ο	CARTRIDGE FILTER 150 SQ. FT. CLEAN & CLEAR SERIES	PENTAIR/PAC FAB	CC150	1
Р	FILTRATION PUMP AND MOTOR, SELFPRIMING, 76 GPM @ 60 FT. HEAD, 1HP, 230 VOLT, 20 AMP 1 PHASE, 2" DISCHARGE UNIT WITH PUMP STRAINER	PENTAIR	WFE-4	1
Q	TURBULENCE PUMP AND MOTOR, SELFPRIMING, 113 GPM @ 60 FT. HEAD, 2 HP, 230 VOLT, 20 AMP 1 PHASE, 2" DISCHARGE UNIT WITH PUMP STRAINER	PENTAIR	WFE-8	1
R	BALL VALVE, 2" SLIP X SLIP	SPEARS	2612-020	5
S	VACUUM GAGE, 0" TO 30", 2-1/2" DIA.	ASHCROFT	GB20PA02LKVAC	1
Т	PRESSURE GAUGE, 0 TO 60 PSI, 2-1/2 DIA.	AHSCROFT	B20PA02RK60	2
U	FLOW METER, 2" 20 TO 125 GPM SCALE	BLUE WHITE	F30200P	1
V	BROMINATOR, AUTOMATIC TYPE, OFF LINE	HAYWARD	CL-220	1
X	COMMERCIAL POOL & SPA CONTROL SYSTEM PROVIDES ELECTRONIC COUNTDOWN TIMER AND EMEGENCY SHUTOFF SWITCH (TO DISABLE ALL PUMPS) W/ ALARM	COMPOOL	LX802L	1